

ELEKTRA Heating Cables

Single-side power supply DM

ELEKTRA DM Heating Cables are ready-to-install heating sets which are produced in accordance with IEC 800. A thin heating cable of the length depending on the model, has factory connected cold tail cable. This system is designed for indoor use and direct heating. Should be installed directly under the surface to be heated in either flexible tile adhesive or a self-leveling mix.



This package contains:

- ELEKTRA heating cable (on a spool),
- instruction manual.

> Technical data:

Power output:	10 W/m
Power supply:	230 V
Diameter of cable:	4,3 mm
Min. installation temperature:	+5°C
Max. working temperature:	+80°C
Conduit cables:	1 x 2,5 m; 2 x 0,75 mm ²
Type of heating cable:	double-core, conductor screen, single-side power supply
Insulation:	FEP/PVDF
Outer sheath:	heat resistant PVC
Resistance tolerance:	±5%
Min. radius of bending cable:	5 D
Produkt certificates:	B
Certificate of ISO 9001:	IQ NET, PCBC
Produkt mark:	CE



TYPE	LENGTH	POWER
-	m	W
DM 10/90	9	90
DM 10/130	13	130
DM 10/150	15	150
DM 10/220	22	220
DM 10/280	28	280
DM 10/320	32	320
DM 10/400	40	400
DM 10/450	45	450
DM 10/550	55	550
DM 10/690	69	690
DM 10/780	78	780
DM 10/980	98	980
DM 10/1100	110	1100

ATTENTION: Values shown in the table may vary by up to 5%.

> **Accessories:**

Temperature controllers - page 27-32, 36-37